LUBRPO-V



CLEVERTRONICS L10 Ultrablade Pro Wall Mount Flag Style Exit



PRODUCT INFORMATION		
MIC	AUA01310030002	
Description	L10 Lithium Nanophosphate Ultrablade Pro Blade Exit - Wall mount flag style vertical decal arrangment, Enabled with Clevertest Plus	
Construction	PC/ABS body with PC diffuser	
Mounting	Recessed Wall Mount, Single or Double Sided	
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)	
Cut-Out	350mm x 48mm	
Weight	1.1kg	
Operating Mode	Maintained	
Testing System	Clevertest Plus Enabled (Not activated by default)	
Battery	Lithium Nanophosphate, 3.3V 2500mAh	
Charging Method	Intelligent current limited constant voltage	
Diffuser	Vertical legend, all directional inserts included in the box	
Lamp(s)	12 x LED, 100,000 hours	
Operating Voltage	220-240V AC; 50Hz	
Power Consumption	2.5 Watts (Standby), 3.9 Watts (Max)	
Inrush Current (Max)		
Earth Leakage		
IP Rating	IP20	
Operating Temperature	1°C to 40°C	
AS2293 Classification	C0=E1.25, C90=B1.25	
Viewing Distance	24m	
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3	
Compliance Marking (RCM	A	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530050	Battery
8002178	Emergency LED Panel
AUM01370010002 LUBPRO-CKIT	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

