

CLEVERTRONICS L10 ULTRABLADE PRO



PRODUCT INFORMATION

Catalogue Number	LUBPRO
MIC	UKA01310030002
Description	L10 Lithium Nanophosphate Ultrablade Pro Blade Exit with Clevertest Plus Enabled
Construction	PC/ABS body with PC Diffuser
Mounting	Recessed Ceiling
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)
Ceiling Hole Cut-Out	350mm x 48mm
Minimum Ceiling Depth	80mm
Weight	1.1kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	12 x LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.9 Watts (Standby), 4.1 Watts (Max)

PRODUCT INFORMATION

Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) 			
Luminaire Classification	X	1	AG	180

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	BATTERY:L10 3.3V 2.5AH 70mm lead,no Brkt
8002178	PCA:UBP LED strip PCB Assy (CT10602-Dx)
UKM01370030002	LUBPRO-CKIT-70, Ultrablade Pro, Control Only, L10, 70mA

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.