



LUBPRO

Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, Clevertest Plus, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	LUBPRO			
MIC	UKA01310030003			
Description	Ultrablade Pro Exit, Recessed Ceiling Mount, L10 Nanophosphate, Clevertest Plus, All Pictograms, Single or Double Sided			
Construction	PC/ABS body with PC Diffuser			
Mounting	Recessed Ceiling			
Dimensions L x W x H	317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate)			
Cut-Out	350mm x 48mm			
Minimum Depth	80mm			
Weight	1.1kg			
Operating Mode	Maintained			
Testing System	Clevertest Plus			
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent current limited constant voltage			
Diffuser	All directional inserts included in the box			
Lamp(s)	12 x LED, 100,000 hours			
Operating Voltage	240V AC; 50Hz			
Supply Current	0.038A			
Power Factor	0.446			
Power Consumption	3.8W (Lamps ON Max), 1.6W (Lamps ON Standby)			
Inrush Current (Peak/Duration)	13.08A/84µs			
Earth Leakage	0.331mA			
Viewing Distance	30m			
Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Operating Temperature	0°C to 40°C			
Luminaire Classification	X	1	AFG	180
Compliance Marking				
Appliance Class	Class II double insulated			
Conformity	BS EN 60598-2-22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533050	Battery
UKM01370030003	Emergency Driver
8002178	LED Panel

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.