


LVELED-FMCLEVERTRONICS L10 HIGH IMPACT SECURITY EXIT, FLAG MOUNT





PRODUCT INFORMATION	
Part Number	LVELED-FM
MIC	AUA01330010002
Description	L10 Optimum Cleverfit PRO Exit in Vandal Resistant Case, Flag Mounted, Enabled with Clevertest Plus
Construction	Strong Steel Body with PC Diffusers
Mounting	Single or Double Side Flag Mounted
Dimensions L x W x H	425mm x 100mm x 270mm
Weight	6.6kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 3.9 Watts (Max)
Inrush Current (Max)	13A, 82uS
Earth Leakage	386mA
IP Rating	IP20
Impact Rating	IK12
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D3.2 C ₉₀ =E8
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	&

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530030	Battery
8002710	LED Strip
8003090	Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

