




## LVELED-WM-HVG

Vandal Resistant Exit, Wall Mount, L10 Nanophosphate, Zoneworks XT Hive  
2.4GHz, All Pictograms, Single Sided



Tamperproof screws

### PRODUCT INFORMATION

Part Number	LVELED-WM-HVG
MIC	AUA01930020001
Description	Vandal Resistant Exit, Wall Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, All Pictograms, Single Sided
Construction	Strong Steel Body with PC Diffusers
Mounting	Single Sided Wall Mount
Dimensions L x W x H	425mm x 100mm x 270mm
Weight	6.6kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 3.9 Watts (Max)
IP Rating	IP20
Impact Rating	IK12
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D3.2 C <sub>90</sub> =E8
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead,noBRKT
8002710	PCA:DurisLED Strip Clvrft Pro CT10276-D3
8003152	PCA:CCF-Pro #CT10622 6C40 DReg, Hive
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.