



LVELED-WM

CLEVERTRONICS L10 HIGH IMPACT SECURITY EXIT, WALL MOUNTED



PRODUCT INFORMATION					
Part Number	LVELED-WM				
MIC	UKA01330020001				
Description	L10 Optimum Cleverfit PRO Exit in vandal resistant case, wall mounted				
Construction	Strong Steel Body with PC Diffusers				
Mounting	Single Sided Wall Mount				
Dimensions L x W x H	425mm x 100mm x 270mm				
Weight	6.6kg				
Operating Mode	Maintained				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	All directional inserts included in the box				
Lamp(s)	6 x Duris E3 LED, 100,000 hours				
Operating Voltage	220-240V AC; 50Hz				
Power Consumption	3.4 Watts (Standby), 4.2 Watts (Max)				
Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Impact Rating	IK12				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AG</td><td>180</td></tr></table>	X	1	AG	180
X	1	AG	180		
Conformity	BS EN 60598.2.22, BS 5266				

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



LVELED-WM

CLEVERTRONICS L10 HIGH IMPACT SECURITY EXIT, WALL MOUNTED

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	Battery
8002710	LED Strip
8003167	Driver

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice