



LVP2LEDM-P-DD-HV

Argonaut Vandal Resistant 600mm Weatherproof Emergency Batten,
L10 Nanophosphate with POD, DALI Driver, Zoneworks XT Hive



PRODUCT INFORMATION

Part Number	LVP2LEDM-P-DD-HV
MIC	AUB01830120002
Description	Argonaut Vandal Resistant 600mm Weatherproof Emergency Batten, L10 Nanophosphate with POD, DALI Driver, Zoneworks XT Hive
Construction	Pressure die-cast, low copper aluminium alloy body with powder coat paint finish Removable gear tray and replaceable LED modules
Mounting	Surface Mount
Dimensions L x W x H	790mm x 140mm (Batten) x 120mm (POD width 136mm)
Weight	3.2kg
Operating Mode	Maintained
Testing System	Zoneworks Hive
Battery	Lithium Nanophosphate, 6.6V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Opal, Impact Resistant Polycarbonate with Secure Access Screws, LSZH
Driver / Ballast	Tridonic LC 50W 350-1050mA, ONEFORALL
Lamp(s)	1 x LED module, 4000K natural white, 100,000h [L80/ B20, Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.9
Inrush Current (Max)	21.642A
Earth Leakage	0.245mA
Power Consumption	26W (MAX Charge - Lamp ON), 21W (Standby Lamp ON), 1W (Standby Lamp OFF)
Total Lumen Output	2529 lm @ 109lm/W
Operating Temperature	0°C to 40°C
IP Rating	IP66
Impact Rating	IK10
AS2293 Classification	C0=D100 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530260	Battery
1330056	240V Driver
8002754	Emergency LED Panel
AUM01870630001 LCPLED-4W-CKIT-HVEXTA-HBL	Emergency Driver
8003182	Emergency Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.