



LVP4LEDM-P-D2

Argonaut Vandal Resistant 1200mm Weatherproof Emergency Batten,
L10 Nanophosphate with POD, DALI-2 Emergency



PRODUCT INFORMATION

Part Number	LVP4LEDM-P-D2
MIC	AUB00000042101
Description	Argonaut Vandal Resistant 1200mm Weatherproof Emergency Batten, L10 Nanophosphate with POD, DALI-2 Emergency
Construction	Pressure Die-cast, Low Copper Aluminium Alloy Body with Grey Powder Coat Paint Finish. Removable Gear Tray and Replaceable LED Modules. Battery POD at one end. (Retains Through-Conduit/Wiring Capability even with the POD).
Mounting	Surface Mount
Dimensions L x W x H	1400mm x 140mm x 120mm (including battery POD)
Weight	5.1kg
Operating Mode	Maintained
Testing System	DALI-2 Emergency
Battery	Lithium Nanophosphate, 6.6V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Opal, Impact Resistant Polycarbonate with Secure Access Screws
Driver / Ballast	Tridonic LC 50W 350-1050mA
Lamp(s)	LED strip module, 4000K, Ra(CRI)>80 L70/B50 Ta 40°C; Reported > 60,000h, Projected 184,000hr L80/B20 Ta 40°C; Reported 60,000h, Projected 100,000h L90/B10 Ta 40°C; Reported 43,000h, Projected 43,000h L70/B50 Ta 25°C; Reported > 102,000h, Projected 275,000h L80/B20 Ta 25°C; Reported > 102,000h, Projected 137,000h L90/B10 Ta 25°C; Reported 61000, Projected 61000h
Operating Voltage	220-240V~ 50Hz
Total Lumen Output	5632lm @ 129.5lm/W
Power Factor	0.85
Power Consumption	1.2W (STDBY OFF) 39.7 (STDBY ON) 43.5W (MAX)
Inrush Current (Peak/Duration)	20.21
Earth Leakage	0.103mA
IP Rating	IP66
Impact Rating	IK11
LED MacAdam Step (SDCM)	3
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D100, C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530260	Battery
8002755	Emergency LED Panel
AUM00000005501	Emergency Driver
1330055	240V Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.