



LVP4LEDM-P-DD-D2

Argonaut Vandal Resistant 1200mm Weatherproof Emergency Batten, L10 Nanophosphate with POD, DALI-2 Driver, DALI-2 Emergency



PRODUCT INFORMATION

Part Number	LVP4LEDM-P-DD-D2
MIC	UKB00000020001
Description	Argonaut Vandal Resistant 1200mm Weatherproof Emergency Batten, L10 Nanophosphate with POD, DALI-2 Driver, DALI-2 Emergency
Construction	Pressure Die-cast, Low Copper Aluminium Alloy Body with Grey Powder Coat Paint Finish. Removable Gear Tray and Replaceable LED Modules. Battery POD at one end. (Retains Through-Conduit/Wiring Capability even with the POD)
Mounting	Surface Mount
Dimensions L x W x H	1400mm x 140mm x 120mm
Weight	5.2kg
Operating Mode	Maintained
Testing System	DALI-2 Emergency
Battery	Lithium Nanophosphate, 6.6V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Opal, Impact Resistant Polycarbonate with Secure Access Screws, LSZH
Driver / Ballast	Tridonic LCA 50W 350-1050mA ONE4ALL
Lamp(s)	LED strip module, 4000K, (CRI) Ra>90 L70/B50 Ta 40 °C: Reported >120,000h, Projected 226,600h L80/B20 Ta 40 °C: Reported >120,000h, Projected 134,600h L90/B10 Ta 40 °C: Reported 63,600h, Projected 63,600h
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Power Consumption	49W (MAX Charge Lamp ON), 46W (Standby Lamp ON), 1.2W (Standby Lamp OFF)
Total Lumen Output	5632lm @ 123lm/W (based on non-emergency version)
Operating Temperature	0°C to 40°C
IP Rating	IP66
Impact Rating	IK10
Rated Emergency Duration	180 Minutes
Emergency Lumen Output	305lm
Luminaire Classification	X 2 ADF 180
Conformity	BS 5266-1, BS EN IEC 60598-2-22, BS EN IEC 55015, BS EN IEC 61547, BS EN IEC 61000-3-2, BS EN IEC 61000-3-3, ETSI EN 301 489-1, ETSI EN 301 489-17
Compliance Marking	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1330056	240V Driver
8012110	LED Panel

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order