

LVP4LEDM-P-DD-HVG

CLEVERTRONICS L10 ARGONAUT VANDAL BATTEN
Zoneworks XT HIVE 2.4GHz



PRODUCT INFORMATION	
Part Number	LVP4LEDM-P-DD-HVG
MIC	AUB01930030002
Description	L10 Optimum 4ft Argonaut LED Vandal Batten with Battery POD and LED Modules/Light Engines with DALI Driver
Construction	Pressure Die-cast, Low Copper Aluminium Alloy Body with Grey Powder Coat Paint Finish. Removable Gear Tray and Replaceable LED Modules. Battery POD at one end. (Retains Through-Conduit/Wiring Capability even with the POD)
Mounting	Surface Mount
Dimensions L x W x H	1400mm x 140mm x 120mm (including battery POD)
Weight	5.1kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 6.6V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Opal, Impact Resistant Polycarbonate with Secure Access Screws
Driver / Ballast	Tridonic Driver - LC 50w 350-1050mA, 20-50V
Lamp(s)	LED strip module, 4000K, Ra>80 L70/B50 Ta 40°C; LM80 Report >60,000hr, Projected 184,000hr L80/B20 Ta 40°C; LM80 Report >60,000hr, Projected 100,000hr L90/B10 Ta 40°C; LM80 Report 43,000hr, Projected 43,000hr
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Power Consumption	1.2W (Standby Off), 40.5W (Standby Off), 44.8W (Max)
Total Lumen Output	5632lm @ 129.5lm/W
Operating Temperature	0°C to 40°C
IP Rating	IP66
Impact Rating	IK10
AS2293 Classification	C ₀ =D100 C ₉₀ =50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	&

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530260	Battery
1330056	240V Driver
8002699	Emergency LED Panel
AUM01970430001 LCPLED-4W-CKIT-HVGEXTA-HBL	Emergency Driver
8003590	Emergency Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

