




## LVP4LEDM-P-HVG

Argonaut Vandal Resistant 1200mm Weatherproof Emergency Batten, L10 Nanophosphate with POD, Zoneworks XT Hive



### PRODUCT INFORMATION

Part Number	LVP4LEDM-P-HVG
MIC	AUB01930010002
Description	Argonaut Vandal Resistant 1200mm Weatherproof Emergency Batten, L10 Nanophosphate with POD, Zoneworks XT Hive
Construction	Pressure Die-cast, Low Copper Aluminium Alloy Body with Grey Powder Coat Paint Finish. Removable Gear Tray and Replaceable LED Modules. Battery POD at one end. (Retains Through-Conduit/Wiring Capability even with the POD)
Mounting	Surface Mount
Dimensions L x W x H	1400mm x 140mm x 120mm (including battery POD)
Weight	5.4kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF), 2.4GHz
Battery	Lithium Nanophosphate, 6.6V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Opal, Impact Resistant Polycarbonate with Secure Access Screws
Driver / Ballast	Tridonic LC 50W 350-1050mA
Lamp(s)	LED strip module, 4000K, Ra>80 L70/B50 Ta 40°C; LM80 Report >60,000hr, Projected 184,000hr L80/B20 Ta 40°C; LM80 Report >60,000hr, Projected 100,000hr L90/B10 Ta 40°C; LM80 Report 43,000hr, Projected 43,000hr
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Power Consumption	1.2W (STDBY OFF) 39.7 (STDBY ON) 43.5W (MAX)
Inrush Current (Max)	20.21
Earth Leakage	0.103mA
Total Lumen Output	5632lm @ 129.5lm/W
Operating Temperature	0°C to 40°C
IP Rating	IP66
Impact Rating	IK11
AS2293 Classification	C0=D100, C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530260	Battery
8002755	Emergency LED Panel
AUM01970430001	Emergency Driver
LCPLED-4W-CKIT-HVGEXTA-HBL	
1330055	240V Driver
8003590	Emergency Hive Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.