



LWELED-HV-IPREM

IP66/67 Weatherproof Exit, Surface Mount, L10 Nanophosphate,
Zoneworks XT Hive, All Pictograms, Single or Double Sided,
Weatherproof Remote Control Gear



PRODUCT INFORMATION

Part Number	LWELED-HV-IPREM
MIC	AUA01820190002
Description	IP66/67 Weatherproof Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, All Pictograms, Single or Double Sided, Weatherproof Remote Control Gear
Construction	Polycarbonate clear Cover, Glass reinforced Nylon PA66 Base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	Main Enclosure - 410mm x 100mm x 272mm Control Pack - 380mm x 130mm x 190mm
Weight	3.4kg (Main Enclosure)
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 4.0 Watts (Max)
Inrush Current (Peak/Duration)	17.1A/138µS
Earth Leakage	N/A
IP Rating	IP66/IP67
IK Rating	IK10
Operating Temperature	-40°C to 40°C (Main Enclosure) 0°C to 40°C (Remote Control Pack)
AS2293 Classification	C0=E5, C90=D4, C180=D4, C270=D6.3
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	Battery
8002710	LED Strip
AUM01870920001 LWELED-CKIT-HV-43-83	Driver Pack
8003191	Hive Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.



LWELED-HV-IPREM

IP66/67 Weatherproof Exit, Surface Mount, L10 Nanophosphate,
Zoneworks XT Hive, All Pictograms, Single or Double Sided,
Weatherproof Remote Control Gear

Inter-connecting cable type and distances

In accordance with AS2293, the maximum distance the control gear and battery can be located from the lamp source is 2m before there is a requirement need to run in fire protected cable. Below is a list indicating the maximum distance and cable size required to mount the Weatherproof Exit lamp source 10, 20, 40 & 80m away from the control pack and batteries. Please note that this cable would need to be suitably fire rated. Clevertronics will supply the pack and heads with a short lead and terminal block (contained within each enclosure) for the contractor to supply and wire the appropriate 2-way "extension" cable.

The cable sizes for 10M, 20M, 40M, 80M are as follows:

10M: 1.5 mm²

20M: 1.5 mm²

40M: 2.5 mm²

80M: 2.5 mm²