




LWELED-TH-HVG-R

L10 Weatherproof Exit, Theatre, Zoneworks XT HIVE



PRODUCT INFORMATION

Part Number	LWELED-TH-HVG-R
MIC	AUA01960150001
Description	L10 Optimum Weatherproof Emergency EXIT, Theatre, Zoneworks XT HIVE 2.4GHz
Construction	Polycarbonate Clear Cover, Glass Reinforced Nylon PA66 Base
Mounting	Wall, ceiling single-sided
Dimensions L x W x H	410mm x 100mm x 272mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man (Must specify diffuser combination)
Lamp(s)	6 x LED lamp bar assembly 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8W (Standby), 4.0 W (Max)
Inrush Current (Max)	12.517A, 82uS
Earth Leakage	0.333mA
IP Rating	IP66/IP67
Impact Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =N/A, C ₉₀ =N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	Battery
8002710	LED Strip
8002329	Driver
8003560	HVG Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order