

LWELED-TH-RR

Weatherproof Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow Right, Single Sided



| PRODUCT INFORMATION | |
|--------------------------|--|
| Part Number | LWELED-TH-RR |
| MIC | AUA01360330001 |
| Description | Weatherproof Exit, Surface Mount, L10 Nanophosphate, Clevertest Plus, Theatre Version, Running Man Arrow Right, Single Sided |
| Construction | Polycarbonate clear cover, glass reinforced nylon PA66 base |
| Mounting | Wall, ceiling single-sided |
| Dimensions L x W x H | 410mm x 272mm x 100mm |
| Weight | 3.4kg |
| Operating Mode | Maintained |
| Testing System | Enabled with Clevertest Plus |
| Battery | Lithium Nanophosphate, 3.3V 2500mAh |
| Charging Method | Intelligent current limited constant voltage |
| Diffuser | Theatre mask, Running man Arrow Right |
| Lamp(s) | 6 x LED lamp bar assembly 100,000 hours |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 2.5 Watts (Standby), 3.7 Watts (Max) |
| IP Rating | IP66/67 |
| Operating Temperature | 0°C to 40°C |
| Viewing Distance | 24m |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | <u>&</u> |

| REPLACEMENT PARTS | |
|-------------------|-------------|
| PART NUMBER | DESCRIPTION |
| 1530090 | Battery |
| 8002348 | Driver |
| 8002710 | LED Strip |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

