



LWELED-TH-R

CLEVERTRONICS L10 WEATHERPROOF EXIT, THEATRE



PRODUCT INFORMATION

| | |
|--------------------------|---|
| Part Number | LWELED-TH-R |
| MIC | AUA01360190001 |
| Description | L10 Optimum Weatherproof Exit, Theatre |
| Construction | Polycarbonate Clear Cover, Glass Reinforced Nylon PA66 Base |
| Mounting | Surface Mounted, Single-sided |
| Dimensions L x W x H | 410mm x 272mm x 100mm |
| Weight | 3.4kg |
| Operating Mode | Maintained |
| Testing System | Clevertest Plus |
| Battery | Lithium Nanophosphate, 3.3V 2500mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Diffuser | Theatre Mask, Running Man |
| Lamp(s) | 6 x LED 100,000 Hours |
| Operating Voltage | 220-240V AC; 50Hz |
| Power Consumption | 2.7W (Standby), 4.5W (Max) |
| IP Rating | IP66/67 |
| Operating Temperature | 0°C to 40°C |
| Viewing Distance | 24m |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|-------------|
| 1530090 | Battery |
| 8002430 | LED Panel |
| 8002321 | Driver |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.