




LWELED-WM-FZR

IP66/67 Weatherproof Low Temperature Exit, Wall Mount, L10 Nanophosphate, All Pictograms, Single Sided, Integral Control Gear



PRODUCT INFORMATION

Part Number	LWELED-WM-FZR
MIC	AUA01320150001
Description	IP66/67 Weatherproof Low Temperature Exit, Wall Mount, L10 Nanophosphate, All Pictograms, Single Sided, Integral Control Gear
Construction	Polycarbonate Clear Cover, Polycarbonate Base
Mounting	Wall mount, Single-sided
Dimensions L x W x H	380mm x 190mm x 130mm
Weight	2.7kg
Operating Mode	Maintained
Testing System	Manual testing
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x High Intensity LED, surface mounted onto a replaceable Lamp Bar-100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	1.5 Watts (Standby), 3.3 Watts (Max)
Inrush Current (Max)	12.09A @ 87.3µs
Earth Leakage	0.348mA
IP Rating	IP66/IP67
Operating Temperature	-25°C to 40°C
AS2293 Classification	C ₀ =E1.6 C ₉₀ =C1.6
Impact Rating	IK08 (side surface) IK09 (front surface)
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
AUM01370420002 LLIFEM-PRO-CKIT-NP-50	Driver Pack
8002120	LED Strip

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order