



LWEPRO-FZR-HVG

IP66/67 Weatherproof Low Temperature Exit, Surface Mount,
L10 Nanophosphate, Zoneworks XT Hive,
All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	LWEPRO-FZR-HVG				
MIC	UKA01820020001				
Description	IP66/67 Weatherproof Low Temperature Exit, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, All Pictograms, Single or Double Sided				
Construction	Exit: PC/ABS body with PC diffuser Enclosure: Polycarbonate Clear Cover, Glass reinforced Nylon PA66 Base				
Mounting	Ceiling Mount - Double Sided / Wall Mount - Single Sided				
Dimensions L x W x H	410mm x 100mm x 272mm				
Weight	3.4kg				
Operating Mode	Maintained				
Testing System	Zoneworks XT HIVE (RF)				
Battery	Lithium Nanophosphate, 3.3V 2500mAh				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	All directional inserts included in the box				
Lamp(s)	6 x Duris E3 LED, 100,000 hours				
Operating Voltage	240V AC; 50Hz				
Power Consumption	2.6 Watts (Standby), 3.4 Watts (Max)				
IP Rating	IP66/IP67				
Operating temperature	-25°C to 40°C				
Viewing Distance	30m				
Impact Rating	IK10				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AFG</td><td>180</td></tr></table>	X	1	AFG	180
X	1	AFG	180		
Conformity	BS EN 60598.2.22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	Battery
8002710	LED
8002373	Emergency Driver
8003330	Hive Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order