# LWEPRO-FZR

L10 Optimum Cleverfit PRO Weatherproof Emergency EXIT for Low Temperature Applications

| PRODUCT INFORMATION | |
|---|---|
| Part Number | LWEPRO-FZR |
| MIC | AUA01320160001 |
| Description | L10 Optimum Cleverfit PRO Weatherproof Emergency EXIT for Low Temperature Applications |
| Construction | Exit: PC/ABS body with PC diffuser<br>Enclosure: Polycarbonate Clear Cover, Glass reinforced Nylon PA66 Base |
| Mounting | Ceiling Mount - Double Sided / Wall Mount - Single Sided |
| Dimensions L x W x H | 410mm x 100mm x 272mm |
| Weight | 3.4kg |
| Operating Mode | Maintained, supports 4-Hour Emergency Duration |
| Testing System | Manual |
| Battery | Lithium Nanophosphate, 3.3V 2500mAh |
| Charging Method | Intelligent current limited constant voltage |
| Diffuser | All directional inserts included in the box |
| Lamp(s) | 6 x Duris E2 LED, 100,000 hours |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 1.4 Watts (Standby), 3.5 Watts (Max) |
| IP Rating | IP66/IP67 |
| Impact Rating | IK10 |
| Operating Temperature | -25˚C to 40˚C |
| AS2293 Classification | $C_0$=D2.5 $C_{90}$=E4 |
| Viewing Distance | 24m |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

| REPLACEMENT PARTS | |
|---|---|
| **PART NUMBER** | **DESCRIPTION** |
| 1530030 | BATTERY:L10 3.3V 2.5AH 260mm lead, no Brkt |
| 8002710 | PCA:DurisLED Strip Clvrft Pro CT10276-D1 |
| 8002959 | PCA:CCF-Pro #CT10142-L9 250mA Batt |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order