



LWFLED-HVG-BLK

Supalite IP65 Weatherproof Twin Spot Emergency, Surface Mount, L10
Nanophosphate, Zoneworks XT Hive 2.4GHz, Black



PRODUCT INFORMATION

Part Number	LWFLED-HVG-BLK
MIC	AUE01920020001
Description	Supalite IP65 Weatherproof Twin Spot Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Black
Construction	Polycarbonate
Mounting	Wall Mount (hard wired supply connection)
Dimensions L x W x H	Main enclosure - 380mm x 190mm x 130mm Total height including LED Heads 310mm
Weight	3.6kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	2 x Lithium Nanophosphate, 6.6V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED Heads (adjustable), 495lm per lamp head
Operating Voltage	240V AC; 50Hz
Power Consumption	1.0 Watts (Standby), 5.4 Watts (Max)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=N/A C90=N/A
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530260	BATT:L10. 6.6V 2.5Ah 200m lead.Stck.Brkt. (Qty 2)
1100550	WP Led Head, c/w Led's & Loom, Gland
LCPLED-18V500C-CKIT-HVG	LED Power Pack, 18V 500mA, L10, HVG (incl. Hive node)
8003570	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant Horiz

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order



LWFLED-HVG-BLK

Supalite IP65 Weatherproof Twin Spot Emergency, Surface Mount, L10
Nanophosphate, Zoneworks XT Hive 2.4GHz, Black

Isolux plot and value table for a 30m x 30m area serviced by a Weatherproof Supalite with each LED lamp head tilted down 30°, rolled out 30°. The Weatherproof Supalite mounted on the wall at a height of 3m and 6m (values in lux).

