

## Supalite IP65 Weatherproof Twin Spot Emergency, Surface Mount L10 Nanophosphate, Zoneworks XT Hive 2.4GHz



### PRODUCT INFORMATION

Catalogue Number	LWFLED-HVG
MIC	AUE01920030001
Description	Supalite IP65 Weatherproof Twin Spot Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz
Construction	Polycarbonate
Mounting	Surface wall mount (hard wired supply connection)
Dimensions L x W x H	Main enclosure - 380mm x 190mm x 130mm Total height including LED Heads 310mm
Weight	3.6kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	2 x Lithium Nanophosphate, 6.6V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED Heads (adjustable), 495lm per lamp head
Operating Voltage	240V AC; 50Hz
Power Consumption	1.0 Watts (Standby), 5.5 Watts (Max)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =N/A C <sub>90</sub> =N/A

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530260	BATT:L10. 6.6V 2.5Ah 200m lead.Stck.Brkt. (Qty 2)
LCPLED-WP-18V500C-CKIT	LED Power Pack, 18V 500mA, IP Loom, L10
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order*

Isolux plot and value table for a 30m x 30m area serviced by a Weatherproof Supalite with each LED lamp head tilted down 30°, rolled out 30°. The Weatherproof Supalite mounted on the wall at a height of 3m and 6m (values in lux).

