



LWFLED-HVG

CLEVERTRONICS L10 LED WEATHERPROOF SUPALITE



PRODUCT INFORMATION

Part Number	LWFLED-HVG			
MIC	UKE01820010001			
Description	L10 Optimum LED Weatherproof Supalite Flood Unit, Emergency Light			
Construction	Polycarbonate			
Mounting	Surface wall mount (hard wired supply connection)			
Dimensions L x W x H	Main enclosure - 380mm x 190mm x 130mm Total height including LED Heads 310mm			
Weight	3.6kg			
Operating Mode	Non-maintained			
Testing System	Zoneworks XT HIVE(RF)			
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Lamp(s)	2 x LED Heads (adjustable), 300lm per lamp head			
Operating Voltage	240V AC; 50Hz			
Total Lumen Output	600lm (Emergency)			
Power Consumption	1.0 Watts (Standby), 5.4 Watts (Max)			
Rated Emergency Duration	180 minutes			
IP Rating	IP65			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts			
Luminaire Classification	X	0	ADF	180
Conformity	BS EN 60598-2-22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530260	BATT:L10. 6.6V 2.5Ah..2m lead.Stck.Brkt. (Qty 2)
1100550	WP Led Head, c/w Led's & Loom
UKM01870200001 LCPLED-WP-17V300C-CKIT-HVG	LED Power Pack, 17V 300mA, IP Loom, HVG, OWC, L10 (incl Hive node)
8003335	PCA: 2.4Ghz RF Node CT10748-A1 Int Ant Horiz Con

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice