



LWFLEDM-UPS

CLEVERTRONICS MAINTAINED LED WEATHERPROOF SUPALITE
UPS CONTROLLED



| PRODUCT INFORMATION | |
|--------------------------|--|
| Part Number | LWFLEDM-UPS |
| Description | LED Weatherproof Supalite Flood Unit, Surface Mounted, Maintained Emergency Light. Supplied from a UPS (240VAC) or 220/240VAC/DC changeover supply (NOTE: change over facilities are required external to the luminaire supplied by others) |
| Construction | Polycarbonate |
| Mounting | Surface Wall Mount. Supplied with flex and plug (the flex and plug can be removed to allow for a hard-wired connection) |
| Dimensions | Main enclosure - 380mm (W) x 190mm (H) x 130mm (D) Total height including LED Heads 310mm |
| Weight | 3.6 kg |
| Operating Mode | Maintained with no integral battery backup (UPS) If a 240V AC supply is applied to the luminaire the LED lamp will illuminate. To operate the fitting in Non-Maintained mode an external sensing relay (supplied by others) will be required to sense the loss of supply to the local lighting circuit and facilitate the changeover to the 240V AC backup/UPS supply |
| Testing System | N/A |
| Battery | N/A |
| Charging Method | N/A |
| Lamp(s) | 2 x LED Heads (adjustable), 495lm per lamp head |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 10.5 Watts |
| IP Rating | IP65 |
| Operating Temperature | -25°C to 40°C |
| AS2293 Classification | C ₀ =N/A C ₉₀ =N/A |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

| REPLACEMENT PARTS | |
|-------------------|--|
| PART NUMBER | DESCRIPTION |
| 1100550 | WP Led Head, c/w Led's & Loom, Gland (QTY 2) |
| 1330047 | LED Driver - LC 10w 500mA,fix C SNC |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

IMPORTANT NOTICE

If there are separate supply cables coming to the fitting the contractor must install an additional, external change over relay to facilitate the changeover from the 240V AC cables to the backup 240V AC cables. The fitting only has the capacity to accept one supply input.



LWFLEDM-UPS

CLEVERTRONICS MAINTAINED LED WEATHERPROOF SUPALITE
UPS CONTROLLED

Isolux plot and value table for a 30m x 30m area serviced by a Weatherproof Supalite with each LED lamp head tilted down 30°, rolled out 30°. The Weatherproof Supalite mounted on the wall at a height of 3m and 6m (values in lux).

