



LWFLED

CLEVERTRONICS L10 LED WEATHERPROOF SUPALITE



PRODUCT INFORMATION

Part Number	LWFLED				
MIC	UKE01320010002				
Description	L10 Lithium Nanophosphate LED Weatherproof Supalite Flood Unit, Surface Mounted Emergency Light, Enabled with Clevertest Plus				
Construction	Polycarbonate				
Mounting	Surface wall mount (hard wired supply connection)				
Dimensions L x W x H	Main enclosure - 380mm x 190mm x 130mm Total height including LED Heads 310mm				
Weight	3.6kg				
Operating Mode	Non-maintained				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Lamp(s)	2 x LED Heads (adjustable), 300lm per lamp head				
Operating Voltage	240V AC; 50Hz				
Total Lumen Output	600lm (Emergency)				
Power Consumption	1.0 Watts (Standby), 5.4 Watts (Max)				
Rated Emergency Duration	180 minutes				
IP Rating	IP65				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts				
Luminaire Classification	X	1	AD	180	
Conformity	BS EN 60598.2.22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530260	BATT:L10. 6.6V 2.5Ah..2m lead.Stck.Brkt. (QTY 2)
UKM01370100002	LED Power Pack, 17V 300mA, IP Loom, CTP,OWC, L10
1100550	WP Led Head, c/w Led's & Loom (QTY 2)

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice