

## LWPLIFE-PRO-CM-BLK

## CLEVERTRONICS L10 LIFELIGHT PRO CEILING MOUNT IP65, EMERGENCY LUMINAIRE, BLACK



PRODUCT INFORMATION	v
Part Number	LWPLIFE-PRO-CM-BLK
MIC	AUT01320120002
Description	L10 Optimum LifeLight PRO, IP65 Ceiling Mounted Emergency, Black Clevertest Plus Enabled (Not activated by default)
Construction	Die Cast Aluminium Body Stainless Steel Screws Clear Toughened Glass
Mounting	Ceiling Mounted
Dimensions L x W x H	186mm Diameter x 289mm Height
Operating Mode	Non-maintained
Testing System	Enabled with Clevertest Plus
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the Lamp head and loom Assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)
Inrush Current (Max)	14.080A
Earth Leakage	0.359mA
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530230	Battery
1100872	LED Head
AUM01370120001 LLIFE-PRO-CKIT-NP	Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

