

LWPLIFE-PRO-DALI-WM-BLK

CLEVERTRONICS L10 LIFELIGHT PRO WALL MOUNT, BLACK



PRODUCT INFORMATION	
Part Number	LWPLIFE-PRO-DALI-WM-BLK
MIC	AUT01220170102
Description	L10 Lithium Nanophosphate LifeLight PRO, IP65 wall mounted Emergency Light, Black
Construction	Die Cast Aluminium Body Stainless Steel Screws Clear Toughened Glass
Mounting	Wall Mount
Dimensions L x W x H	287mm x 186mm x 260mm
Weight	5kg
Operating Mode	Non-Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D50, C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	&

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530230	Battery
1100872	LED Head Assembly
AUM01270240002 LLIFE-PRO-CKIT-DALI-NP	Driver Pack
8003060	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

