CLEVERTRONICS L10 LIFELIGHT PRO Wall mount IP65 EMERGENCY LUMINAIRE

 $\Lambda \Lambda$



PRODUCT INFORMATION	
Part Number	LWPLIFE-PRO-DALI-WM-WHT
Description	L10 Lithium Nanophosphate LifeLight PRO, IP65 wall mounted Emergency, White
Construction	Die Cast Aluminium Body Stainless Steel Screws Clear Toughened Glass
Mounting	Wall mount
Dimensions L x W x H	380mm x 135mm x 190mm
Weight	5kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 4.7 Watts (Max)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40
Impact Rating	IK10
REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
1100835	Lifelight Pro Head Assembly, Round,Black
LLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,L10, NP
8003060	PCA: DALI Node #CT10629-Ax



Version: May 2020-1 clevertronics.com.au

