




LWPLIFE-PRO-FZR-HVG

Lifelight Pro IP66/67 Weatherproof Low Temperature Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz



PRODUCT INFORMATION

Part Number	LWPLIFE-PRO-FZR-HVG
MIC	AUT01920080001
Description	Lifelight Pro IP66/67 Weatherproof Low Temperature Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz
Construction	Polycarbonate
Mounting	Surface Mounted
Dimensions L x W x H	380mm x 190mm x 135mm
Weight	3.0kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh (x2)
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby), 3.0W (Max)
IP Rating	IP66/67
IK Rating	IK08
Operating Temperature	-25°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead, Brkt (2)
1100869	Lifelight Pro Head Assembly, Ld:280mm,Rnd,LT,Gen 2
LLIFE-PRO-CKIT-HVG-NP	Lifelight Pro,Control Only, L10, HVG, OWC, NP (incl. Hive node)
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order