



LWPLIFE-PRO-FZR-HVG

CLEVERTRONICS L10 LIFELIGHT PRO WEATHERPROOF
SURFACE MOUNT EMERGENCY FOR LOW TEMPERATURE APPLICATIONS



PRODUCT INFORMATION	
Part Number	LWPLIFE-PRO-FZR-HVG
MIC	UKT01820090001
Description	L10 Optimum Lifelight PRO, IP66/67 Weatherproof, Surface Mounted Emergency Light, for Low Temperature Applications
Construction	Polycarbonate
Dimensions L x W x H	380mm x 190mm x 135mm
Weight	3.0kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type & Manufacturer	Lithium Nanophosphate, 3.3V 5000mAh (x2), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
Total lumen output	330lm

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



LWPLIFE-PRO-FZR-HVG

CLEVERTRONICS L10 LIFELIGHT PRO WEATHERPROOF
SURFACE MOUNT EMERGENCY FOR LOW TEMPERATURE APPLICATIONS

PRODUCT INFORMATION					
Rated Emergency Duration	180 minutes				
IP Rating	IP66/67				
Operating temperature	-25°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts				
Luminaire Classification	<table border="1"><tr><td>X</td><td>0</td><td>ADF</td><td>180</td></tr></table>	X	0	ADF	180
X	0	ADF	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead, Brkt (2)
1100869	Lifelight Pro Head Assembly, Ld:280mm,Rnd,LT,Gen 2
UKM01870140001 LLIFE-PRO-CKIT-HVG-415	LifelightPro,Control Only,Batten,L10,HVG,OWC,415mA (incl. Hive node)
8003330	PCA: 2.4Ghz RF Node CT10748-A1 Int Antenna

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.