



LWPLIFE-PRO-FZR

Lifelight Pro IP66/67 Weatherproof Low Temperature Emergency,
Surface Mount, L10 Nanophosphate



PRODUCT INFORMATION

Part Number	LWPLIFE-PRO-FZR				
MIC	UKT01320010001				
Description	Lifelight Pro IP66/67 Weatherproof Low Temperature Emergency, Surface Mount, L10 Nanophosphate				
Construction	Polycarbonate				
Mounting	Surface Mounted				
Dimensions L x W x H	380mm x 190mm x 135mm				
Weight	3.0kg				
Operating Mode	Non-maintained				
Testing System	Manual testing				
Battery	Lithium Nanophosphate, 3.3V 5000mAh (x2)				
Charging Method	Intelligent Current Limited Constant Voltage				
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)				
Operating Voltage	240V AC; 50Hz				
Total Lumen Output	330lm				
Power Consumption	0.4W (Standby), 2.7W (Max)				
Rated Emergency Duration	180mins				
IP Rating	IP66/67				
Operating Temperature	-25°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Enclosure of lamp control gear provides protection against accidental contacts with live parts				
Luminaire Classification	<table border="1"><tr><td>X</td><td>0</td><td>AD</td><td>180</td></tr></table>	X	0	AD	180
X	0	AD	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery x 2
1100811	LED Head
UKM01370180001 LLIFE-PRO-CKIT-415	Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.