





## LWPLIFE-PRO-HVG-WM-BLK

Lifelight Pro IP65 Weatherproof Cylinder Emergency, Wall Mount, L10  
Nanophosphate, Zoneworks XT Hive 2.4GHz, Black



### PRODUCT INFORMATION

Part Number	LWPLIFE-PRO-HVG-WM-BLK
MIC	AUT01920110001
Description	Lifelight Pro IP65 Weatherproof Cylinder Emergency, Wall Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Black
Construction	Die Cast Aluminium Body, Stainless Steel Screws, Clear Toughened Glass
Mounting	Wall Mount
Dimensions L x W x H	See drawing
Weight	5kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x 3W LED (Lifetime warranty on the Lamp head and loom Assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D50 C <sub>90</sub> =D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.no Brkt
1100872	Lifelight Pro Head Assbly,Ld:280mm,Rnd,LT,Blk,Gen2
LLIFE-PRO-CKIT-HVGEXTA-NP-BLK,	Lifelight Pro, Control Only, HVGEXTA, L10, Blk (incl. Hive node)
8003580	PCA: V5 2.4GHz RF Node CT10816-A1 Ext Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order