



SPIRIT

Spirit Exit, Surface Mount, Trade Series, All Pictograms, Single or Double Sided



PRODUCT INFORMATION

Part Number	SPIRIT
MIC	AUA03510100001
Description	Spirit Exit, Surface Mount, Trade Series, All Pictograms, Single or Double Sided
Construction	Polycarbonate (PC) Body, Polypropylene (PP) Diffuser
Mounting	Wall & Ceiling, Single-Sided & Double-Sided
Dimensions L x W x H	352mm x 80mm x 200mm
Weight	1.0kg
Operating Mode	Can be toggled between maintained and non-maintained mode by pressing the test button 5 times within a 4 second period - default setting is maintained
Testing System	N/A - Manual Test Switch
Battery	Lithium Iron Phosphate, 3.2V 500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All Directional Inserts Included in the Box
Lamp(s)	8 x LED, 50,000 Hours
Projected Light Source Life (LSL)	14Y/05M
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3 Watts (Standby), 2.5 Watts (Max)
Inrush Current (Peak/Duration)	TBD
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E2.5 C90=D2.5
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560180	Battery
8011960	LED Strip
8003550	LED Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.