



CUBPRO-SM-TH-RD

CLEVERTRONICS CLP ULTRABLADE PRO SURFACE MOUNT, THEATRE



PRODUCT INFORMATION	
Part Number	CUBPRO-SM-TH-RD
MIC	UKA02360070001
Description	CLP Premium Ultrablade Pro surface mount blade Exit, Theatre
Construction	PC/ABS body with PC diffuser
Mounting	Surface Mounted Wall, Surface Mounted Ceiling, single-sided
Dimensions L x W x H	317mm x 8.7mm x 157mm (Blade Assembly) 360mm x 47mm x 72mm (Base)
Weight	1.0kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate (LiFePO4)
Charging Method	Intelligent current limited constant voltage
Diffuser	Theatre mask, Running man with Down Arrow
Lamp(s)	12 x Duris E3 LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Viewing Distance	30m
Power Consumption	1.5 Watts (Standby), 3.6 (Max)

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



CUBPRO-SM-TH-RD

CLEVERTRONICS CLP ULTRABLADE PRO SURFACE MOUNT, THEATRE

PRODUCT INFORMATION					
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AG</td><td>180</td></tr></table>	X	1	AG	180
X	1	AG	180		
Applicable Standards	BS EN 60598-2-22, BS 5266				
Compliance Marking					

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550030	Replacement Battery
8002178	Replacement Emergency LED
8003168	Replacement Emergency Driver

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.