




## ZXTELC-HVG

### CLEVERTRONICS ZONEWORKS XT HIVE RF 2.4GHz EMERGENCY LIGHTING CONTROLLER



PRODUCT INFORMATION	
Part Number	ZXTELC-HVG
MIC	AUL00900010002
Description	Zoneworks XT HIVE (RF) 2.4GHz Emergency Lighting Controller (using RevPi Connect+)
Supported Operating Systems	Win10, WinServer 2016, 2019, 2022, Windows 11
Channel Types	Ethernet to RF (2.4GHz)
Ethernet Connector	RJ45 panel mount connector in the side of the enclosure (the Ethernet patch lead and RJ-45 terminating socket to the client network to be supplied by the installer)
Power Supply Interface	Supplied with a 3-core flex and plug (flex and plug can be removed and product hard wired)
Operating Voltage	240V AC; 50Hz
Ethernet Interface	IP via built-in 10/100BaseT Ethernet (DHCP capable and can be used in either static or DHCP mode)
Enclosure	Grey polycarbonate base with a clear polycarbonate cover (see image above) and whip antenna
Dimensions	L=180mm, H=180mm, D=150mm
Mounting	Surface mount via the 4 mounting turrets
Power Consumption	22 Watts, 0.15A @ 240V
Operating Temperature	-40°C to +60°C
Operating Humidity (non-condensing)	10 to 90% RH @ 60°C
Compliance Marking (RCM)	

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.