




ZXTELC-HVG

CLEVERTRONICS ZONEWORKS XT HIVE RF 2.4GHZ
EMERGENCY LIGHTING CONTROLLER



PRODUCT INFORMATION

Part Number	ZXTELC-HVG
MIC	AUL00900010002
Description	Zoneworks HIVE (RF) 2.4GHz Emergency Lighting Controller. Uses an industrial-grade RevPi Compute Module.
Supported Operating Systems	Linux Debian
Emergency Network	RF HVG 2.4GHz V5 Wirepas
Ethernet Connector	RJ45 panel mount connector, IP65 with appropriately rated patch lead. Patch lead connects to client network and supplied by installer.
Power Supply Interface	Supplied with a 3-core flex and plug (flex and plug can be removed and product hard wired)
Operating Voltage	240VAC, 50Hz
Ethernet Interface	IP via built-in 10/100BaseT Ethernet (DHCP capable and can be used in either fixed IP or DHCP mode)
Enclosure	Grey polycarbonate base with a clear polycarbonate cover (see image above) and whip antenna
Dimensions	L=180mm, H=180mm, D=150mm
Mounting	Surface mount via the 4 mounting turrets
Power Consumption	22 Watts, 0.15A @ 240V
Operating Temperature	+1°C to +40°C
Operating Humidity (non-condensing)	10 to 90% RH @ 60°C
IP Rating	IP65 with appropriately rated Ethernet patch lead
Compliance Marking (RCM)	 R-NZ

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.