



ZXTELC-HVG

CLEVERTRONICS ZONEWORKS XT HIVE RF 2.4GHz
EMERGENCY LIGHTING CONTROLLER



PRODUCT INFORMATION

Catalogue Number	ZXTELC-HVG
MIC	UKL00800010001
Description	Zoneworks XT HIVE (RF) Emergency Lighting Controller (using RevPi Connect+)
Construction / Enclosure	Grey polycarbonate base with a clear polycarbonate cover (see image above) and whip antenna
Dimensions	L=180mm, H=180mm, D=150mm
Mounting	Surface mount via the 4 mounting turrets
Supported Operating Systems	Win10, WinServer 2016, 2019, 2022, Windows 11
Channel Types	RF (2.40-2.48GHz)
Ethernet Connector	RJ45 panel mount connector in the side of the enclosure (the Ethernet patch lead and RJ-45 terminating socket to the client network to be supplied by the installer)
Power Supply Interface	Supplied with a 3-core flex (flex can be removed and product hard wired)
Operating Voltage	240V AC; 50Hz
Ethernet Interface	IP via built-in 10/100BaseT Ethernet (DHCP capable and can be used in either static or DHCP mode)
Power Consumption	22 Watts, 0.15A @ 240V
Operating Temperature	1 to +50°C
Operating Humidity (non-condensing)	10 to 90% RH @ 50°C
IP Rating	IP20

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.