

# SUPALITE



## LED Emergency Flood Light

Equipped with high-powered LED's, the Supalite emergency flood light is a trusted source of light during times of power failure.

Easy to install and featuring high power LED heads that can be adjusted to the required position, they are ideal for schools, hospitals, and office buildings.



### Applications

- |                                                                                               |                                                                                                       |
|-----------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
|  Warehouses |  Car Parks         |
|  Factories  |  Sports Facilities |
|  Schools    |  Railway Stations  |

### Features and Benefits

- AS/NZS 2293.3 compliant
- Low power consumption
- LED adjustable lamps
- Up to 370lm
- Lithium Iron Phosphate or Nanophosphate® battery
- Clevertest Plus System Compatible




# SUPALITE

ORDERING INFORMATION		TS	LP	L10
TEST OPTIONS / PART #	Standard - White	EFLLED-LI	CFLED	LFLED
	Standard - Black	-	CFFLED-BLK	LFFLED-BLK
	Clevertest Plus System Compatible	No	Yes	
	DALI	-	CFFLED-DALI	LFFLED-DALI
	Zoneworks® XT Hive	-	CFFLED-HV	LFFLED-HV
Carton Quantity	10			
Weight - Single (Carton)	1.4kg (15.2kg)			
Dimensions (L x W x H)	Main Enclosure - 282mm x 64mm x 137mm Total Height Including LED Heads 225mm			

POWER, LAMPS AND BATTERY	TS	LP	L10
Power Consumption (Standby / Max)	0.4W / 2.4W	0.4W / 1.7W	0.4W / 2.2W
Lamp(s)	2 x LED Heads (Adjustable)		
Lumen Output (Per Head / Total)	175lm / 350lm	185lm / 370lm	
Battery	Lithium Iron Phosphate		Lithium Nanophosphate®
Voltage / Capacity (mAh)	3.2V / 6000mAh	3.2V / 6400mAh	3.3V / 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage		

TECHNICAL SPECIFICATIONS	TS	LP	L10
Operating Mode	Non-Maintained		
Voltage (V) (Frequency (Hz))	220-240V (50Hz)		
Construction	Polycarbonate		
Operating Temperature	0°C to 40°C		
Ingress Protection Rating (IP)	IP20		

\*Warranty information located at:  
<https://clevertronics.com.au/warranty-statement/>



Dimensions (mm)

**clevertronics.co.nz**  
**clevertronics.com.au**

1 Caribbean Drive, Scoresby VIC 3179  
P +61 3 9559 2700 F +61 3 9559 2799 E [info@clevertronics.com.au](mailto:info@clevertronics.com.au)

Clevertronics is committed to continuously improving its products.  
All features and specifications are subject to change without prior notice.  
\_PRODUCT SHEETS – ANZ Supalite Emergency 07FEB23

