



CLEVERTRONICS LP JUMBO LED EXIT UNIVERSAL MOUNT (DALI)



PRODUCT INFORMATION

Catalogue Number	CJELED-40-DALI
Description	LP Premium Jumbo Emergency Exit
Construction	Powder coated Metal Frame with Acrylic Diffuser
Mounting	Surface Mount
Dimensions L x W x H	630mm x 320mm x 100mm
Weight	7.3kg
Operating Mode	Maintained
Testing System	DALI compatible
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All pictograph directional inserts included in the box (One box solution)
Lamp(s)	12 x High Intensity LED, Surface Mounted onto a Replaceable Lamp Bar - 100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	3.2 Watts (Standby), 5.6 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D6.3 C ₉₀ =E3.2
Viewing Distance	40m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
CJELED-40-CKIT-110	Jumbo LED Exit, Control Kit, LP
8002470	PCA:Duris E5 Strip for LJELED.CT10050-D1
8002200	PCA:DALI Node, #CT10410-A3

DALI EM

LP LITHIUM IRON
PHOSPHATE
PREMIUM
PROVEN PROJECT PERFORMANCE