



CLEVERTRONICS L10 ARGONAUT VANDAL BATTEN



PRODUCT INFORMATION

| | |
|-----------------------|---|
| Catalogue Number | LVP4LED-M-P |
| Description | L10 Optimum 4ft Argonaut LED Vandal Batten with Battery POD and LED Modules/Light Engines, Enabled with Clevertest Plus |
| Construction | Pressure Die-cast, Low Copper Aluminium Alloy Body with Grey Powder Coat Paint Finish. Removable Gear Tray and Replaceable LED Modules. Battery POD at one end. (Retains Through-Conduit/Wiring Capability even with the POD) |
| Mounting | Surface Mount |
| Dimensions L x W x H | 1400mm x 140mm x 120mm (including battery POD) |
| Operating Mode | Maintained |
| Testing System | Clevertest Plus Enabled (Not activated by default) |
| Battery | Lithium Nanophosphate, 6.6V 2500mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Diffuser | Opal, Impact Resistant Polycarbonate with Secure Access Screws |
| Driver / Ballast | Tridonic LC 50W 350-1050mA |
| Lamp(s) | 2 x LED module, 4000K natural white, 50,000h [L80/ B20, Ta 40°C], Ra>80 |
| Operating Voltage | 240V AC; 50Hz |
| Power Factor | > 0.9 |
| Total lumen output | 5300 lm @ 123lm/W |
| Power Consumption | 44 Watts (Lamps ON), 0.4 Watts (Lamps OFF) |
| IP Rating | IP66 |
| Operating Temperature | 0°C to 40°C |
| AS2293 Classification | C ₀ =D100 C ₉₀ =D40 |
| Impact Rating | IK10 |
| Viewing Distance | N/A |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|--------------------|--|
| 1530260 | BATT:L10 6.6V 2500mA.SBS. |
| 1330055 | LED Driver - LC 50w 1050mA, flc Ip EXC |
| 8002699 | PCA: LED Strip 5P8S, ALS-50-840-3-01-A |
| LCPLED-48V95C-CKIT | LED Power Pack, 48V 95mA, 6.6V 2.5Ah,L10 |

