

# VANDAL RESISTANT EXIT



## A Strong, Robust and Reliable Exit

The Vandal Resistant Exit is a high impact IK12 rated exit that utilises the Cleverfit PRO within a powder coated steel enclosure.

It provides an effective solution for prisons, correction facilities, train stations and heavy industrial areas. It can be wall, ceiling or flag mounted with single or double-sided decals.



### Applications

- |   |   |
|---|---|
|  Public Amenities |  Schools                 |
|  Stadiums         |  Train Stations          |
|  Car Parks        |  Correctional Facilities |

### Features and Benefits

- AS/NZS 2293.3 compliant
- Wall, ceiling and flag mount options
- All directional decals in one box
- Lithium Nanophosphate® battery
- Clevertest Plus System compatible
- All test options available



# VANDAL RESISTANT EXIT

		L10		
ORDERING INFORMATION		CEILING MOUNTED	WALL MOUNTED	FLAG MOUNTED
TEST OPTIONS / PART #	Standard	LVELED-CM	LVELED-WM	LVELED-FM
	Clevertest Plus System Compatible	Yes		
	DALI	LVELED-CM-DALI	LVELED-WM-DALI	LVELED-FM-DALI
	Zoneworks® XT Hive	LVELED-CM-HV	LVELED-WM-HV	LVELED-FM-HV
Carton Quantity		1		
Weight - Single (Carton)		6.6kg		
Dimensions (L x W x H)		425mm x 100mm x 270mm		
Directional Options		All Directional Inserts Included		

POWER, LAMPS AND BATTERY		L10		
Power Consumption (Standby / Max)		3.6W / 5.6W		
Lamp(s)		100,000 Hours		
Battery		Lithium Nanophosphate®		
Voltage (V) / Capacity (mAh)		3.3V / 2500mAh		
Charging Method		Intelligent Current Limited Constant Voltage		

TECHNICAL SPECIFICATIONS	
Operating Mode	Maintained
Voltage (V) (Frequency (Hz))	220-240V (50Hz)
Construction	Cleverfit Pro Inside Powder Coated Metal Frame & PC Diffuser
Viewing Distance	24m
Operating Temperature	1°C to 40°C
Ingress Protection Rating (IP)	IP20
Impact Rating (IK)	IK12 (Wall & Ceiling Mounted) IK10 (Flag Mounted)


CLASSIFICATION	L10		
	CEILING MOUNTED	WALL MOUNTED	FLAG MOUNTED
C0	D3.2	D3.2	D3.2
C90	E8	E8	E8

SPACING TABLE AND MOUNTING HEIGHTS – AS/NZS 2293.1:2018 (MINIMUM LIGHT LEVEL OF 0.2 LUX)									
Classification	2.1m	2.4m	2.7m	3.0m	3.3m	3.6m	4.0m	4.5m	5.0m
D3.2	6.5	6.5	6.5	6.5	6.3	6.1	5.8	0.0	0.0
E8	7.3	7.9	8.4	8.8	9.2	9.5	9.9	10.2	10.4

For 1 lux and AS/NZS 2293.1:2005 spacing tables please visit: <https://clevertronics.com.au/spacing-tables/>

Based on minimum light level of 0.2 lux.  
Maximum allowed mounting height is 2.7m but for exceptions see AS/NZS 2293.1.  
Spacing classifications do not apply for theatre versions.

\*Warranty information located at:  
<https://clevertronics.com.au/warranty-statement/>



Dimensions (mm)

**clevertronics.co.nz**  
**clevertronics.com.au**

1 Caribbean Drive, Scoresby VIC 3179  
P +61 3 9559 2700 F +61 3 9559 2799 E [info@clevertronics.com.au](mailto:info@clevertronics.com.au)

Clevertronics is committed to continuously improving its products.  
All features and specifications are subject to change without prior notice.  
\_PRODUCT SHEETS – ANZ Vandal Resistant 04OCT22

