

## CLEVERTRONICS L10 LIFELIGHT PRO CYLINDER SURFACE MOUNT EMERGENCY LIGHT (DALI)



### PRODUCT INFORMATION

Catalogue Number	LLIFE-PRO-SMC-DALI
MIC	AUT01210410102
Description	L10 Optimum Lifelight PRO, High Performance, Cylinder Surface Mount Emergency Light
Construction	Powder coated metal enclosure, PC/ABS head
Mounting	Surface mount
Dimensions	120mm Diameter x 252mm Height
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	Dali Registered
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	3.0W (Max), 0.7W (Standby)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D80 C <sub>90</sub> =D80

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
8003080	PCA: LLPRO HEAD Alum #CT10640-D3
AUM01270250102 LLIFE-PRO-SMC-CKIT-DALI-NP	LifelightPro,Control Only, SMC, Dali Reg, L10, NP (incl. Dali Node)
8003060	PCA: DALI Node #CT10629-Ax

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order*