




LWPLIFE-PRO-HV-WM-WHT

CLEVERTRONICS L10 LIFELIGHT PRO
IP65 WALL MOUNT EMERGENCY LUMINAIRE - WHITE



PRODUCT INFORMATION	
Part Number	LWPLIFE-PRO-HV-WM-WHT
MIC	AUT01820260001
Description	L10 Optimum LifeLight PRO, IP65 Wall Mounted Emergency Luminaire, White
Construction	Die Cast Aluminium Body, Stainless Steel Screws, Clear Toughened Glass
Mounting	Wall Mount
Dimensions L x W x H	See drawing
Weight	5kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x 3W LED (Lifetime warranty on the Lamp head and loom Assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D50 C ₉₀ =D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.no Brkt
1100869	Lifelight Pro Head Assembly, Ld:280mm,Rnd,LT,Gen 2
AUM01870170001	LLIFE-PRO-CKIT-HVEXTA-NP, Lifelight Pro, Control Only, HVEXTA, L10 (incl. Hive node)
8003194	PCA: RF Node CT10678-A12 Ext Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order