



LLIFE-PRO-SMC-DALI-BLK

CLEVERTRONICS L10 LIFELIGHT PRO CYLINDER
SURFACE MOUNT EMERGENCY - BLACK



PRODUCT INFORMATION

Catalogue Number	LLIFE-PRO-SMC-DALI-BLK
MIC	AUT01210420003
Description	L10 Optimum Lifelight PRO, High Performance, Cylinder Surface Mount Emergency Light, Black
Construction	Powder coated metal enclosure, PC/ABS head
Mounting	Surface Mount
Dimensions	128mm Diameter, 245mm Height
Weight	1.9kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
1100872	Lifelight Pro Head Assbly,Ld:280mm,Rnd,LT,Blk,Gen2
AUM01270250102 LLIFE-PRO-SMC-CKIT-DALI-NP	Lifelight Pro,Control Only, SMC, Dali Reg, L10, NP (incl DALI node)
8003060	PCA: New DALI #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.