



## LLIFEM-PRO-SMC-SA-BLK

CLEVERTRONICS L10 LIFELIGHT PRO CYLINDER  
SURFACE MOUNT EMERGENCY



### PRODUCT INFORMATION

Catalogue Number	LLIFEM-PRO-SMC-SA-BLK
MIC	AUT01310520001
Description	L10 Optimum Lifelight PRO, High Performance, Cylinder Surface Mount Emergency Light, Maintained (switched active on/off control of LED's)
Construction	Powder coated metal enclosure, PC/ABS head
Mounting	Surface Mount
Dimensions	128mm Diameter, 245mm Height
Weight	1.9kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 2.4 Watts (Maintained Standby), 4.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
1100872	LED Head Assembly
AUM01370580001 LLIFEM-PRO-SMC-SA-CKIT-NP	Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.