



CLIFE-PRO-SMC-HV

CLEVERTRONICS LP LIFELIGHT PRO CYLINDER
SURFACE MOUNT EMERGENCY



PRODUCT INFORMATION

Catalogue Number	CLIFE-PRO-SMC-HV
MIC	AUT02810100002
Description	LP Premium Lifelight PRO, High Performance, Cylinder Surface Mount Emergency Light
Construction	Powder coated metal enclosure, PC/ABS head
Mounting	Surface Mount
Dimensions L x W x H	128mm Diameter, 245mm Height
Weight	1.9kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
AUM02870250001 CLIFE-PRO-SMC-CKIT- HVEXTA-NP	Lifelight Pro, Control Only, SMC, HV, LP, NP (incl Hive node)
8003081	PCA: LLPRO HEAD Alum #CT10640-D4 - GW CSHPM 'LT'
8003194	PCA: RF Node CT10678-A7 Ext Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.