



LWPLIFE-PRO-HV-CM-BLK

CLEVERTRONICS L10 LIFELIGHT PRO IP65 WEATHERPROOF
CEILING MOUNT EMERGENCY - BLACK



PRODUCT INFORMATION	
Part Number	LWPLIFE-PRO-HV-CM-BLK
MIC	AUT01820100001
Description	L10 Optimum LifeLight PRO, IP65 Ceiling Mounted Emergency, Black
Construction	Die Cast Aluminium Body, Stainless Steel Screws, Clear Toughened Glass
Mounting	Ceiling Mounted
Dimensions Diameter x Height	186mm x 294mm
Weight	3.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x 3W LED (Lifetime warranty on the Lamp head and loom Assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
1100817	Lifelight Pro Head Assembly, Round, LT, Blk, Gen 2
AUM01870520001 LLIFE-PRO-CKIT-HVEXTA-NP-BLK	Lifelight Pro, Control Only, HVEXTA, L10, Blk (incl. Hive node)
8003194	PCA: RF Node CT10678-A12 Ext Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order