



CLIFE-PRO-SMC-BLK

CLEVERTRONICS LP LIFELIGHT PRO CYLINDER
SURFACE MOUNT EMERGENCY - BLACK



PRODUCT INFORMATION

Catalogue Number	CLIFE-PRO-SMC-BLK
MIC	AUT02310160002
Description	LP Premium Lifelight PRO, High Performance, Cylinder Surface Mount Emergency Light, Black, Enabled with Clevertest Plus
Construction	Powder coated metal enclosure, PC/ABS head
Mounting	Surface Mount
Dimensions	128mm Diameter, 245mm Height
Weight	1.9kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
AUM02370220001 CLIFE-PRO-SMC-CKIT-NP	Lifelight Pro, Control Only, SMC, LP, NP, OWC
8003081	LED: PCA: LLPRO HEAD Alum #CT10640-D4 - GW CSHPM 'LT'

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.