

# LIFELIGHT PRO SURFACE MOUNT WEATHERPROOF



## High Performance Weatherproof LED Emergency Luminaire

The Lifelight Pro Surface Mount Weatherproof emergency luminaire has a D80 classification and is designed for use in applications where an IP65 rating is required.

The slimline high impact IK08 polycarbonate enclosure makes installation easy and provides robustness in open areas.



### Applications



Apartments



Aquatic Centers



Schools



Public Buildings



Car Parks

**LP** LITHIUM IRON  
PHOSPHATE  
PREMIUM  
PREMIUM PROJECT PERFORMANCE

**L10** LITHIUM  
NANOPHOSPHATE®  
OPTIMUM  
NOTHING ELSE COMPETES WITH NANOPHOSPHATE®

### Features and Benefits

- AS/NZS 2293.3 compliant
- D80 emergency classification
- IP65 and IK08
- Low 0.4W power consumption
- Lithium Iron Phosphate or Nanophosphate battery
- Warehouse lens version available
- Clevertest Plus System compatible
- Available in white or black



# LIFELIGHT PRO SURFACE MOUNT WEATHERPROOF

ORDERING INFORMATION		LP	L10
Type		Integral Battery	Integral Battery
TEST OPTIONS / PART #	Standard - White	CLIFE-PRO-SM-WP	LLIFE-PRO-SM-WP
	Clevertest Plus System Compatible	Yes	
	DALI	CLIFE-PRO-SM-WP-DALI	LLIFE-PRO-SM-WP-DALI
	Zoneworks® XT Hive	CLIFE-PRO-SM-WP-HV	LLIFE-PRO-SM-WP-HV
Carton Quantity		10 Pieces	
Weight - Single (Carton)		0.8kg	0.8kg
Dimensions (L x W x H)		247mm x 129mm x 51mm	247mm x 129mm x 51mm

POWER, LAMPS AND BATTERY		LP	L10
Power Consumption (Standby / Max)*		0.4W / 2.7W	0.4W / 2.7W
Lamp(s)		Dual LED	
Battery		Lithium Iron Phosphate	Lithium Nanophosphate®
Voltage (V) / Capacity (mAh)		3.2V / 6400mAh	3.3V / 5000mAh
Charging Method		Intelligent Current Limited Constant Voltage	


TECHNICAL SPECIFICATIONS		CLASSIFICATION		LP	L10
Operating Mode	Non-Maintained	C0	D80	D80	D80
Voltage (V) (Frequency (Hz))	240V AC (50HZ)				
Operating Temperature	0°C to 40°C	C90	D80	D80	D80
Ingress Protection Rating (IP)	IP65				

SPACING TABLE AND MOUNTING HEIGHTS – AS/NZS 2293.1:2018 (MINIMUM LIGHT LEVEL OF 0.2 LUX)														
Classification	2.1m	2.4m	2.7m	3.0m	3.3m	3.6m	4.0m	4.5m	5.0m	6.0m	7.0m	8.0m	9.0m	10.0m
D80	11.5	13.2	14.8	16.5	18.1	19.8	22	24.7	27.5	28.9	30	30.9	31.5	32.1

■ Care should be taken when spacing luminaires at the distances indicated by the shaded regions to ensure conformance to AS/NZS2293.1, Clause 4.3 is maintained. A single emergency luminaire shall not serve an area of greater than 500 m².

For 1 lux and AS/NZS 2293.1:2005 spacing tables please visit: <https://clevertronics.com.au/spacing-tables/>

\*Warranty information located at: <https://clevertronics.com.au/warranty-statement/>



Dimensions (mm)

**clevertronics.co.nz**  
**clevertronics.com.au**

1 Caribbean Drive, Scoresby VIC 3179  
P +61 3 9559 2700 F +61 3 9559 2799 E [info@clevertronics.com.au](mailto:info@clevertronics.com.au)

Clevertronics is committed to continuously improving its products.  
All features and specifications are subject to change without prior notice.  
\_PRODUCT SHEETS – ANZ Lifelight Pro Surface Mount Weatherproof 04OCT22

