

# GIGANTOR EXIT



## 80m Viewing Distance Exit

The Gigantor Exit caters for applications requiring viewing distances of up to 80m.

With LED and Lithium battery technology the Gigantor is perfect for stadiums and large hall usage. Featuring a robust steel housing with a 510mm high pictograph that is designed to be wall mounted.



### Applications



Factories



Stadiums



Warehouses



Halls

### Features and Benefits

- AS/NZS 2293.3 compliant
- Wall mount
- Can be rod or chain suspended
- Lithium Iron Phosphate battery
- Clevertest Plus System compatible



# GIGANTOR EXIT

ORDERING INFORMATION		LP
TEST OPTIONS / PART #	Standard	CGELED-80-WM-R
	Clevertest Plus System Compatible	Yes
	DALI	CGELED-80-WM-DALI-R
	Zoneworks® XT Hive	CGELED-80-WM-HV-R
Carton Quantity	1	
Weight - Single (Carton)	21kg	
Dimensions (L x W x H)	1305mm x 170mm x 560mm	
Directional Options	Must Specify Diffuser Combination	

POWER, LAMPS AND BATTERY		LP
Power Consumption (Standby / Max)	23W / 30W	
Lamp(s)	100,000 Hours LED 2 x 3W LED	
Battery Type	Lithium Iron Phosphate	
Voltage (V) / Capacity (mAh)	1 x 3.2V / 6400mAh 1 x 6.4V / 3200mAh	
Charging Method	Intelligent Current Limited Constant Voltage	


TECHNICAL SPECIFICATIONS		CLASSIFICATION	LP
Operating Mode	Maintained	C0	D80
Voltage (V) Frequency (Hz)	220-240V (50Hz)	C90	D80
Construction - Body / Diffuser	Powder Coated Metal / Acrylic		
Viewing Distance	80m		
Mounting Type	Wall Single Sided		
Operating Temperature	1°C to 40°C		
Ingress Protection Rating (IP)	IP20		

SPACING TABLE AND MOUNTING HEIGHTS – AS/NZS 2293.1:2018 (MINIMUM LIGHT LEVEL OF 0.2 LUX)									
Classification	2.1m	2.4m	2.7m	3.0m	3.3m	3.6m	4.0m	4.5m	5.0m
D80	11.5	13.2	14.8	16.5	18.1	19.8	-	-	-

For 1 lux and AS/NZS 2293.1:2005 spacing tables please visit: <https://clevertronics.com.au/spacing-tables/>

Based on minimum light level of 0.2 lux.  
Maximum allowed mounting height is 2.7m but for exceptions see AS/NZS 2293.1.  
Spacing classifications do not apply for theatre versions.

\*Warranty information located at:  
<https://clevertronics.com.au/warranty-statement/>



Dimensions (mm)

**clevertronics.co.nz**  
**clevertronics.com.au**

1 Caribbean Drive, Scoresby VIC 3179  
P +61 3 9559 2700 F +61 3 9559 2799 E [info@clevertronics.com.au](mailto:info@clevertronics.com.au)

Clevertronics is committed to continuously improving its products.  
All features and specifications are subject to change without prior notice.  
\_PRODUCT SHEETS – ANZ Gigantor 04OCT22

