


# LIFELIGHT SURFACE MOUNT WEATHERPROOF



## Weatherproof LED Emergency Luminaire



The Lifelight Surface Mount Weatherproof emergency luminaire is designed for use in applications where an IP65 rating is required.

The slimline high impact IK08 polycarbonate enclosure makes installation easy and provides robustness in open areas.

### Applications

- |   |   |
|---|---|
|  Office Buildings |  Apartments      |
|  Schools          |  Aquatic Centers |
|  Car Parks        |   |

### Features and Benefits

- AS/NZS 2293.3 compliant
- Low power consumption
- D40 or D50 emergency classification
- IP65 and IK08
- Lithium Iron Phosphate or Nanophosphate battery
- Corridor lens version available
- Clevertest Plus System compatible
- Available in white or black



**TRADE**  
SERIES  
THE TRADES CHOICE

**LP** LITHIUM IRON PHOSPHATE  
PREMIUM  
PREMIUM PROJECT PERFORMANCE

**L10** LITHIUM NANOPHOSPHATE<sup>®</sup>  
OPTIMUM  
NOTHING ELSE COMPETES WITH NANOPHOSPHATE<sup>®</sup>

# LIFELIGHT SURFACE MOUNT WEATHERPROOF

ORDERING INFORMATION	TS	LP	L10
Type	Integral	Integral	Integral
TEST OPTIONS / PART #			
Standard - White	ELIFE-X-LI-SM-WP	CLIFE-SM-WP	LLIFE-SM-WP
Clevertest Plus System Compatible	Yes		
DALI	-	CLIFE-SM-WP-DALI	LLIFE-SM-WP-DALI
Zoneworks® XT Hive	-	CLIFE-SM-WP-HV	LLIFE-SM-WP-HV
Carton Quantity	10 Pieces		
Weight - Single (Carton)	0.8kg	0.8kg	0.8kg
Dimensions (L x W x H)	247mm x 129mm x 51mm	247mm x 129mm x 51mm	247mm x 129mm x 51mm

POWER, LAMPS AND BATTERY	TS	LP	L10
Power Consumption (Standby / Max)*	0.4W / 1.3W	1W / 4.2W	1W / 4.2W
Lamp(s)	LED		
Battery	Lithium Iron Phosphate	Lithium Iron Phosphate	Lithium Nanophosphate®
Voltage (V) / Capacity (mAh)	3.2V / 3200mAh	3.2V / 3200mAh	3.3V / 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage		

TECHNICAL SPECIFICATIONS	CLASSIFICATION*	TS	LP	L10
Operating Mode		Non-Maintained		
Voltage (V) (Frequency (Hz))		240V (50HZ)		
Operating Temperature		0°C to 40°C		
Ingress Protection Rating (IP)		IP65		
Impact Rating (IK)		IK08		
	C0	D50	D50	D40
	C90	D50	D50	D40


\* Excludes corridor lens

SPACING TABLE AND MOUNTING HEIGHTS – AS/NZS 2293.1:2018 (MINIMUM LIGHT LEVEL OF 0.2 LUX) - EXCLUDES CORRIDOR LENS														
Classification	2.1m	2.4m	2.7m	3.0m	3.3m	3.6m	4.0m	4.5m	5.0m	6.0m	7.0m	8.0m	9.0m	10.0m
D40	11.5	13.2	14.8	16.5	18.1	19.5	20.1	20.7	21.2	22.1	22.6	23.0	23.1	23.0
D50	11.5	13.2	14.8	16.5	18.1	19.8	21.8	22.5	23.1	24.1	24.9	25.4	25.7	25.8

■ Care should be taken when spacing luminaires at the distances indicated by the shaded regions to ensure conformance to AS/NZS2293.1, Clause 4.3 is maintained. A single emergency luminaire shall not serve an area of greater than 500 m².

For 1 lux and AS/NZS 2293.1:2005 spacing tables please visit: <https://clevertronics.com.au/spacing-tables/>

\*Warranty information located at: <https://clevertronics.com.au/warranty-statement/>



Dimensions (mm)

**clevertronics.co.nz**  
**clevertronics.com.au**

1 Caribbean Drive, Scoresby VIC 3179  
P +61 3 9559 2700 F +61 3 9559 2799 E [info@clevertronics.com.au](mailto:info@clevertronics.com.au)

Clevertronics is committed to continuously improving its products. All features and specifications are subject to change without prior notice. PRODUCT SHEETS – ANZ Lifelight Surface Mount Weatherproof 04OCT22

