CLEVERTRONICS LP LED WEATHERPROOF BUNKALITE, GREY (ZONEWORKS XT HIVE)

PRODUCT INFORMATION	
Catalogue Number	CBKLEDS-HV-GRY
Description	LP Premium Bunkalite IP65 Weatherproof Emergency Luminaire, Grey
Construction	Base Material: Die-cast aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	Diamater 360mm, Depth 145mm
Weight	4.5kg
Operating Mode	Sustained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver / Ballast	Constant current, 500mA, 50,000hrs
Lamp(s)	LED module, 4,000K natural white, 50,000h life, Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.9
Total lumen output	1400 lm @ 82lm/W (87lm/W non-emergency version)
Power Consumption	17 Watts (Lamp ON), 1.0 Watts (Lamp OFF)
IP Rating	IP65
Operating Temperature	0˚C to 40˚C
AS2293 Classification	C_0=D25 C_{90}=D25
Impact Rating	IK10

REPLACEMENT PARTS	
PART NUMBER	**DESCRIPTION**
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
AUM02870100001	Lifelight, Control Only, HV, LP, No Plug
1330051	LED Driver - LC 20w 500mA, SC ADV
8003195	PCA: RF Node CT10678-A7 Ext Antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order